



Specifications Cordstrap AnchorLash® 105.4

Performance Specifications			
Solution Breaking Strength*	12.000 daN / 26.455 lbf (±10%)		
Solution MSL	9.000 daN / 219.841 lbf (±10%)		
Certification	Mariterm, Eurosafe, DNV-GL witnessed		

Specifications Cordstrap AnchorLash 1	05.4				
Construction & Dimensions	Four horizontal woven lashings	Four horizontal woven lashings joined by 4 buckles. Each lashing has a			
	stitched soft loop at the end to	stitched soft loop at the end to secure it to the container anchor point.			
Designed for	Rigid packaging, Soft packaging, Drums, IBC´s, FIBC´s (big bags)				
Horizontal Element Woven Lashing	4.5 meter / 14.8' (±2%) – 2 pie	4.5 meter / 14.8' (±2%) – 2 pieces			
- Length (red)	5.5 meter / 18' (±2%) – 2 p	5.5 meter / 18' (±2%) – 2 pieces			
- Length (orange)	6.5 meter / 21.3' (±2%) – 2 pie	ces			
- Length (yellow)	7.5 meter / 24.6' (±2%) – 2 pie	7.5 meter / 24.6' (±2%) – 2 pieces			
- Length (white)	32 mm / 1.25" (±5%)				
- Width	≤ 9%				
- Elasticity		- F			
Heavy duty buckle	35 mm / 1.4" (±5%)	35 mm / 1.4" (±5%)			
- Width					
Packaging	PalletBox	SmallBox			
Pieces per Box	110	6			
Box Weight	378 kg / 833 lbs	20 kg / 44 lbs			
Box Dimensions	1200 x 800 x 776 mm	400 x 400 x 250 mm			
Item number	7256915	7256910			
Material					
Lashing	High tenacity polyester filamer	High tenacity polyester filament yarn			
Buckle	Silver zinc coated dropforged s	Silver zinc coated dropforged steel buckle			
Packaging	The solution is packed in a pla	The solution is packed in a plastic bag (recycling 4) and corrugated			
	fiberboard (recycling code 20)	fiberboard (recycling code 20)			



Represented in over 50 countries

World market leader ISO 9001 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance





Recommended Tensioner(s)						
Battery Tensioner CBT 35	Pneumatic Tensioner CT 35 PN	Manual Tensioner CT 40 (2)				
Product Code EU Type (incl. charger, 2	Product code	Product code				
batteries)	7567000	7502400				
7850001						
Product Code US Type (incl. charger, 2						
batteries)						
7580021						
Product Code Global Type (incl. 2 batteries)						
7580031						
Product Code Global Type (incl. charger)						
7580051						

Recommended Accessories					
Container Magnets	Applicator Tool	Cargo protection			
Packaging	Packaging	Vertical hang Strap			
2 pieces per box	1 piece per box	Retainer buckles			
		Reefer lashing point			
Product Code	Product Code				
7555000	7608200	*see more information in Add-Ons			
		Commercial spec. sheet to find			
		products for supporting your			
		application			

Links to instruction sheet						
	Ū.			\Box		
Steel drums	Plastic drums	IBC's	Soft packaging	Small big bags	High big bags	Crates/boxes

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°f and 104°f. All information provided is based on accuracy at time of creation.



Represented in over 50 countries

World market leader ISO 9001 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance