



Specifications Cordstrap CornerLash® 105.4 20 FT

Performance Specifications				
Solution Breaking Strength* Solution MSL Certification	12.000 daN / 26,400 lbf (±10%) 9.000 daN / 19,800 lbf (±10%) Mariterm, Eurosafe, DNV-GL witnessed			

Specifications Cordstrap CornerLash 105.4 20 FT

Construction & Dimensions

Four Horizontal pieces of woven lashing joined by 4 buckles. Each part of lashing is looped through Corner element* included in the Corner post**. Dedicated to 20-foot containers.

* Corner element – patented external anchor point

Rigid packaging, Soft packaging, Drums, IBC's, FIBC's (big bags)

 $\mbox{**}$ Corner post - ISO standardized load-carrying element, part of the steel framework of box container

Designed for

Lashing

LengthWidthElasticityColor

Heavy duty buckle
- Width

Corner element
Corner element spring

Packaging

Pieces per Box Boxes on pallet Box Weight

Box Dimensions Item number

Material Lashing

Corner element
Corner element spring

Buckle Packaging 15 m / 49.2' (±2%) – 4 pieces

32 mm / 1.25" (±5%)

≤ 9% white

35 mm / 1.4" (±5%)

4 pieces 4 pieces

Cardboard box

64

9.52 kg / 20.99 lbs 285 x 186 x 200 mm

7256588

High tenacity polyester filament yarn

Galvanized steel

Silver zinc coated dropforged steel buckle

The solution is packed in corrugated fiberboard (recycling code 20)



Represented in over 50 countries

World market leader
ISO 9001 certified
Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance





Recommended Tensioner(s)							
Battery Tensioner CBT 35	Pneumatic Tensioner CT 35 PN	Manual Tensioner CT 40 (2)					
Product Code EU Type (incl. charger, 2 batteries)	Product code	Product code					
7850001	7567000	7502400					
Product Code US Type (incl. charger, 2 batteries)							
7580021							
Product Code Global Type (incl. 2 batteries)							
7580031							
Product Code Global Type (incl. charger)							
7580051							

Recommended Accessories	
Container Magnets	Cargo protection
Packaging	See more information in Add-Ons Commercial spec. sheet to find products for
2 pieces per box	supporting your application
Product Code	
7555000	

Links to instruction sheet							
Steel drums	Plastic drums	IBC's	Soft packaging	Small big bags	High big bags	Crates/boxes	
Coordstrap	Cordstraps	Cordstrept	ordstrept	Grandstrep-X	Condition of	Condition	

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°f and 104°f. All information provided is based on accuracy at time of creation.



Represented in over 50 countries World market leader ISO 9001 certified Manufacturer & supplier since 1965

Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance