



# Specifications Cordstrap CornerLash® 105.4 40 FT

Performance Specifications				
Solution Breaking Strength* Solution MSL Certification	12.000 daN / 26,400 lbf (±10%) 9.000 daN / 19,800 lbf (±10%) Mariterm, Eurosafe, DNV-GL witnessed			

#### Specifications Cordstrap CornerLash 105.4 40 FT

Construction & Dimensions

Four Horizontal pieces of woven lashing joined by 4 buckles. Each part of lashing is looped through Corner element\* included in the Corner post\*\*. Dedicated to 40-foot

\* Corner element – patented external anchor point

Rigid packaging, Soft packaging, Drums, IBC's, FIBC's (big bags)

\*\* Corner post - ISO standardized load-carrying element, part of the steel framework of box container

### Designed for

#### Lashing

Length Width Elasticity Color

Heavy duty buckle Width

Corner element Corner element spring

#### **Packaging**

Pieces per Box Boxes on pallet **Box Weight** 

**Box Dimensions** Item number

## Material

Lashing Corner element Corner element spring

Buckle Packaging 30 m / 98.4' (±2%) – 4 pieces

32 mm / 1.25" (±5%)

≤ 9% white

35 mm / 1.4" (±5%)

4 pieces 4 pieces

# Cardboard box

48

12 kg / 26.5 lbs 285 x 186 x 200 mm

7256688



High tenacity polyester filament yarn

Galvanized steel Galvanized steel

Silver zinc coated dropforged steel buckle

The solution is packed in corrugated fiberboard (recycling code 20)

### Recommended Tensioner(s)



Represented in over 50 countries

World market leader ISO 9001 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance





Battery Tensioner CBT 35	Pneumatic Tensioner CT 35 PN	Manual Tensioner CT 40 (2)
Product Code EU Type (incl. charger, 2 batteries)	Product code	Product code
7850001	7567000	7502400
Product Code US Type (incl. charger, 2 batteries)		
7580021		
Product Code Global Type (incl. 2 batteries)		
7580031		
Product Code Global Type (incl. charger)		
7580051		

Recommended Accessories	
Container Magnets Packaging	Cargo protection See more information in Add-Ons Commercial spec. sheet to find products for
2 pieces per box	supporting your application
Product Code	
7555000	

Links to instruction sheet							
Steel drums	Plastic drums	IBC's	Soft packaging	Small big bags	High big bags	Crates/boxes	
Coordstrap	Condition	Cordstrept	Cordstrept	Grandstrap A	Condition of	Condition	

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°f and 104°f.

All information provided is based on accuracy at time of creation.



Represented in over 50 countries

World market leader
ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance